BlindSelection

Blind Measuring Worksheet

Size calculator and full guide:
blindselection.com/how-to-measure-for-blinds
Version: November 2026

- Steel tape. Nearest 1/8 inch.
- Inside width: top, middle, bottom. Order the narrowest.
- Inside height: left, center, right. Order the longest.
- On a 1/16 mark: width down, height up.
- Don't take deductions. The factory does it.
- Outside mount: at least 2 1/2" extra on each side.

Window / room _____ **Mount** ☐ Inside ☐ Outside

	1	2	3	Order this
Width (top / mid / bottom)				narrowest, round down
Height (left / center / right)				longest, round up
Depth (3 points)				smallest vs product min.

Cranks, latches, locks in the way? _____ **Product / color** _____

Window / room _____ **Mount** ☐ Inside ☐ Outside

	1	2	3	Order this
Width (top / mid / bottom)				narrowest, round down
Height (left / center / right)				longest, round up
Depth (3 points)				smallest vs product min.

Cranks, latches, locks in the way? _____ **Product / color** _____

Window / room _____ **Mount** ☐ Inside ☐ Outside

	1	2	3	Order this
Width (top / mid / bottom)				narrowest, round down
Height (left / center / right)				longest, round up
Depth (3 points)				smallest vs product min.

Cranks, latches, locks in the way? _____ **Product / color** _____

Outside mount only _____

	Measured	+ extra	Order this
Width (opening or trim)		+ 5" min. (2 1/2" each side)	
Height (headrail to stop)		+ space above frame	

Notes _____

Before you order: width first, then height. Pick the same mount you measured for. The product's own measuring guide always wins.